

COPY FOR IB

PATENT COOPERATION TREATY

PCT

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY
(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

REC'D 12 MAY 2006



WIPO

PCT

Applicant's or agent's file reference P04TS14/PCT	FOR FURTHER ACTION		See Form PCT/IPEA/416
International application No. PCT/KR2004/002061	International filing date(day/month/year) 18 AUGUST 2004 (18.08.2004)	Priority date (day/month/year) 19 AUGUST 2003 (19.08.2003)	
International Patent Classification (IPC) or national classification and IPC IPC7 B41J 3/407			
Applicant TAEIL SYSTEMS CO., LTD. et al			

- This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36.
- This REPORT consists of a total of 4 sheets, including this cover sheet.
- This report is also accompanied by ANNEXES, comprising:
 - ☒ (sent to the applicant and to the International Bureau) a total of 35 sheets, as follows:
 - ☒ sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions);
 - ☐ sheets which supersede earlier sheets, but which this Authority considers contain an amendment that goes beyond the disclosure in the international application as filed, as indicated in item 4 of Box No. I and the Supplemental Box.
 - ☐ (sent to the International Bureau only) a total of (Indicate type and number of electronic carrier(s)) _____ containing a sequence listing and/or tables related thereto, in computer readable form only, as indicated in the Supplemental Box relating to Sequence Listing (see Section 802 of the Administrative Instructions).

- This report contains indications relating to the following items:
 - ☒ Box No. I Basis of the report
 - ☐ Box No. II Priority
 - ☐ Box No. III Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
 - ☐ Box No. IV Lack of unity of invention
 - ☒ Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
 - ☐ Box No. VI Certain documents cited
 - ☐ Box No. VII Certain defects in the international application
 - ☐ Box No. VIII Certain observations on the international application

Date of submission of the demand 02 NOVEMBER 2004 (02.11.2004)	Date of completion of this report 30 NOVEMBER 2005 (30.11.2005)
Name and mailing address of the IPEA/KR  Korean Intellectual Property Office 920 Dunsan-dong, Seo-gu, Daejeon 302-701, Republic of Korea Facsimile No. 82-42-472-7140	Authorized officer CHUNG, Sang Tac Telephone No. 82-42-481-5497 

Form PCT/IPEA/409 (cover sheet) (January 2004)

BEST AVAILABLE COPY

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/KR2004/002061

Box No. I Basis of the report

1. With regard to the **language**, this report is based on the international application in the language in which it was filed, unless otherwise indicated under this item.
 - ☒ This report is based on translations from the original language into the following language English, which is the language of a translation furnished for the purposes of:
 - ☐ international search (under Rules 12.3 and 23.1(b))
 - ☒ publication of the international application (under Rule 12.4)
 - ☐ international preliminary examination (under Rules 55.2 and/or 55.3)

2. With regard to the **elements** of the international application, this report is based on (*replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report*):
 - ☐ the international application as originally filed/furnished
 - ☒ the description:
 - pages none as originally filed/furnished
 - pages* 1-19 received by this Authority on 17 March 2005
 - pages* none received by this Authority on _____
 - ☒ the claims:
 - pages none as originally filed/furnished
 - pages* none as amended (together with any statement) under Article 19
 - pages* 20-23 received by this Authority on 17 March 2005
 - pages* none received by this Authority on _____
 - ☒ the drawings:
 - pages 1-7 as originally filed/furnished
 - pages* none received by this Authority on _____
 - pages* none received by this Authority on _____
 - ☐ the sequence listing and/or any related table(s) - see Supplemental Box Relating to Sequence Listing.

3. ☐ The amendments have resulted in the cancellation of:
 - ☐ the description, pages _____
 - ☐ the claims, Nos. _____
 - ☐ the drawings, sheets _____
 - ☐ the sequence listing (*specify*): _____
 - ☐ any table(s) related to sequence listing (*specify*): _____

4. ☐ This report has been established as if (some of) the amendments annexed to this report and listed below had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).
 - ☐ the description, pages _____
 - ☐ the claims, Nos. _____
 - ☐ the drawings, sheets _____
 - ☐ the sequence listing (*specify*): _____
 - ☐ any table(s) related to sequence listing (*specify*): _____

* If item 4 applies, some or all of those sheets may be marked "superseded."

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.
PCT/KR2004/002061

Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)	Claims	1-7	YES
	Claims	none	NO
Inventive step (IS)	Claims	1-7	YES
	Claims	none	NO
Industrial applicability (IA)	Claims	1-7	YES
	Claims	none	NO

2. Citations and explanations (Rule 70.7)

The following documents have been considered for the purpose of this written opinion:

D1: KR 2002-1446 A
D2: JP 2001-026198 A
D3: US 6106174 A

1. Prior Art

D1 relates to a media supply controller of a digital printing machine comprising a supply motor, a pulling motor, and a sensor, wherein according to the winding or unwinding of said media, the rotation and stop of said supply and pulling motors are controlled.

D2 relates to a paper-moving-type plotter, and discloses the structure for taking up a paper sheet delivered forward and backward of a platen without sag.

D3 discloses a printing machine for a plastic tile with a feeding correction device comprising a central electric sensing eye disposed on a first layer of the plastic tile for detecting a position of the tile.

2. Subject-Matter

The invention of claim 1 relates to a digital textile printer for preventing a printing material from being wrinkled and warped, comprising tension means at the bottom of the front and rear of legs, for rotating eccentrically at a predetermined angle; position sensors for sensing the position of said tension means; and a feeding motor and a rewinding motor,

(Continued on Supplemental Sheet.)

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/KR2004/002061

Supplemental Box

In case the space in any of the preceding boxes is not sufficient.
Continuation of:

Box V.

3. Novelty and Inventive Step

The invention of claim 1 is the same as the inventions of D1–D3 in the technical field of printing materials such as a fiber through feeding or rewinding features and in the winding of the printing materials by tension without lag.

The subject matter of claim 1 consists in the control of feeding and rewinding motors by detecting by sensors the position of tension means for rotating eccentrically at a predetermined angle. None of said documents D1–D3 teach or fairly suggest said subject matter of claim 1, and it would be non-obvious to a person skilled in the art to derive said subject matter from the teachings of D1–D3.

Therefore, the subject matter of claim 1 is considered to be novel and to involve an inventive step.

Since Claims 2–7 are dependent on claim 1, the subject matter of claims 2–7 is also considered to be novel and to involve an inventive step.

4. Industrial Applicability

The subject matter of claims 1–7 is considered to be industrially applicable.

Title

Digital textile printer

5 Field of the Invention

The present invention relates to a digital textile printer, and more particularly a printer performing effectively not only general printing operations to a little thick printing material (textile fabrics or papers), such as a banner, a advertising material, or a photograph, but also textile printing operations to the very thin printing material, such as textile fabrics.

15 Description of the Related Art

Generally, in the conventional printer utilizing a technique of subtractive mixture, a digital controller sends digitalized signals to a head of the printer, so that the head may inject proper amounts of ink of three primary colors comprising magenta, yellow, and cyan, and of a black color to a printing material to produce various color tones. Therefore, the latest printer makes it possible for a user

to design more easily what she/he wants.

In the technique of subtractive mixture, the head of the printer equips several ink reservoirs, while each ink reservoir contains one color respectively. The head injects proper amounts of ink from each reservoir to produce a new color tone. The head often equips another ink reservoir containing special color to produce a new color tone, if necessary.

By referencing Fig. 1 and Fig. 2, the conventional digital printer will be described briefly in the following statements.

The conventional printer equips a transfer belt with a rail shape on the top of a base 3, while the base 3 is supported by both legs 1 contacting with the ground. The one side of a cartridge 9 is fixed with the transfer belt 5, so that a head 7 of the cartridge 9 can be moved through the transfer belt 5. In more, a transfer axis 50 is connected with a transfer motor (not shown) within a driving panel 18 installed in the one side of the inner upper side of the base 3. Additionally, lots of transfer rollers 51 on the transfer axis 50 are extruded on the top of the base 3 to make a printing material 17 move to the forward direction, while a press roller 40 equipped

correspondingly on the top of each transfer roller 51 presses the printing material 17 to the downward direction.

In more, a feeding roller 11 installed in the rear side of the digital printer supplies the printing material 17 to the top of the base 3. When the cartridge 9 moves reciprocally to the left or the right direction on the top of the printing material 17, the head 7 moving in combination with the cartridge 9 injects predetermined amounts of each color from the corresponding ink reservoir to perform printing operations. As a result, the printed material is recoiled in a rewinding roller 12 located on the opposite side of the feeding roller 11.

An operation panel 16 covered by a cover 15 is equipped on the top of the base 3. Therefore, a user can input any desirable signal to be printed in the printing material 17.

In other words, as shown in Fig. 2, the printing material 17 is suspended to the feeding roller 11 in the rear of a fixing frame 10 between the legs 1, and the end of the printing material 17 passes through the top of the base 3 supported by the legs 1. In more, the rewinding roller 12 winding the printing material 17 printed at the base 3 is in the front of the fixing frame 10.

However, the conventional printer described in the above statements has the following problems. After the printing material 17 is put between lots of transfer rollers 51 and press rollers 40, the transfer roller 51 rotates to make the printing material 17 move to the front side of the base 3. When the printing material 17 is extremely thin in the case of textile printing, the speed of the printing material 17 passing through between the transfer rollers 51 and the press rollers 40 is different from that of the printing material 17 before the transfer roller 51. Therefore, a portion of the printing material 17 is often wrinkled, and the wrinkled moving printing material 17 has a tendency of inclining toward one direction only. As a result, when the printing material 17 is distorted or wrinkled, printing colors are overlapped to get high fraction defective of the printing operations.

Additionally, the conventional digital printer does not have a feeding means drawing and rewinding the printing material 17 in constant speed to maintain the printing material 17 in plain. Therefore, the distortion or the wrinkle of the printing material 17 is deepened more to increase fraction defective of the printing operation.

Detailed Description of the Invention

To overcome the above described problems, the present invention provides a digital textile printer comprising the front rewinding and the rear feeding devices, at the front and the rear of the base, driven by a transfer axis in a driving panel, winding a printing material to a rewinding roller in a constant tension force, preventing defective printing operations generated by distorting or wrinkling phenomena of the printing material, and performing effective textile printing to the very thin textile fabrics eventually.

In more, the present invention provides a digital textile printer comprising a long ink-retrieving hole, on the top of the base, collecting the residues of the injected ink passing through the printing material to prevent the printing material from ink contamination or ink smearing.

In more, the present invention provides a digital textile printer comprising a heater of rubber material, in the inside of the front of the base, drying promptly the printing material passing through the ink-retrieving hole.

To achieve the above described purpose, the present

invention discloses a digital textile printer with a transfer belt with a rail shape on the top of the base supported by both legs contacted with the ground, a cartridge transferable through the transfer belt and fixing
5 a head unit at the one side of the cartridge, a transfer axis with a long shape coupled with a transfer motor in a driving panel installed on the top of the inside of a base, multiple transfer rollers of the transfer axis protruding to the top of the base to make a printing material move to
10 the forward direction, a feeding roller means installed in the rear of the base sending the printing material through the top of the base, a rewinding roller means rewinding the printing material from the top of the base, comprising: at least one rear guiding roller means at the rear of the base,
15 coupled with the transfer axis; a rear feeding device including a rear tension means at the bottom of the rear of the legs to rotate eccentrically in a predetermined angle, a rear position sensor installed at a predetermined position of the rear tension means to correspond to a rear
20 eccentric axis of the rear tension means winding the printing material, and a feeding motor installed on the top of the rear tension means to drive a rear bobbin axis of the feeding roller means combined with a rear bobbin

feeding the printing material by receiving signals from the rear position sensor; at least one front guiding roller means at the front of the base, linked with the transfer axis; and a front rewinding device including a front
5 tension means at the bottom of the front of the legs to rotate eccentrically in a predetermined angle, a front position sensor installed at a predetermined position of the front tension means to correspond to a front eccentric axis of the front tension means winding the printing
10 material, and a rewinding motor installed on the top of the front tension means to drive a front bobbin axis of the rewinding roller means combined with a front bobbin rewinding the printing material by receiving signals from the front position sensor.

15 In more, the front tension means installed at the front of the bottom of the legs, comprises: front fixtures facing each other at the front of two legs; a front rotation axis installed eccentrically between two front brackets with a predetermined length, penetrating two front
20 brackets, and both ends of the front rotation axis combined with the front fixtures; and a front eccentric axis, corresponding to the printing material, apart in a

predetermined distance from the front rotation axis between the two front brackets.

In more, the rear tension means installed at the rear of the bottom of the legs, comprises: rear fixtures facing each other at the rear of two legs; a rear rotation axis installed eccentrically between two rear brackets with a predetermined length, penetrating two rear brackets, and both ends of the rear rotation axis combined with the rear fixtures; and a rear eccentric axis, corresponding to the printing material, apart in a predetermined distance from the rear rotation axis between the two rear brackets.

In more, the front guiding roller means further comprises multiple front rollers coupled with the transfer belt of the transfer axis and combined with at least one front tension axis.

In more, the rear guiding roller means further comprises multiple rear rollers coupled with the transfer belt of the transfer axis and combined with at least one rear tension axis.

In more, the diameter of the front roller of the front guiding roller means linked directly with the transfer axis is slightly larger than the diameter of the rear roller of the rear guiding roller means.

In more, the digital textile printer further comprises an ink-retrieving hole in a long shape on the top of the base to collect the residues of the injected ink passing though the printing material.

5 In more, the digital textile printer further comprises a heater of rubber material at the inside of the base to dry promptly the printing material.

In more, the digital textile printer according to claim 1, further comprises: multiple front adjusting holes
10 between the two front brackets; and a front tension adjusting axis installed in one of the multiple front adjusting holes to balanc with the weight of the front eccentric axis, and eventually to adjust tension strength of the front eccentric axis.

15 In more, the digital textile printer according to claim 1, further comprises: multiple rear adjusting holes between the two rear brackets; and a tension rear adjusting axis installed in one of the multiple rear adjusting holes to balanc with the weight of the rear eccentric axis, and
20 eventually to adjust tension strength of the rear eccentric axis.

Brief Description of the Drawings

For a more complete understanding of the present invention and the advantages thereof, reference is now made
5 to the following descriptions taken in conjunction with the accompanying drawings, in which like reference numerals denote like parts, and in which:

Fig. 1 is a perspective view of the conventional printer;

10 Fig. 2 is a schema of the transferring states of a printing material of Fig. 1;

Fig. 3 is a perspective view of the front of a digital textile printer of the present invention;

15 Fig. 4 is a cross sectional view of the main part of the digital textile printer through the line A-A according to the present invention;

Fig. 5 is a perspective view of the rear of the digital textile printer of the present invention;

20 Fig. 6 is a perspective view of the main part of a guiding roller means of the present invention; and

Fig. 7 is a schema describing the printing states of a printing material according to the present invention.

PCT/KR2004/002061

IPEA/KR 1.7.0 3.2005

<DELETED>

5

10

15

20

Embodiment

Reference will now be made in detail to preferred
embodiments of the present invention, example of which is
5 illustrated in the accompanying drawings.

Fig. 3 is a perspective view of the front of a large
sized printer, and Fig. 5 is a perspective view of the rear
of the large sized printer according to the present
invention.

10 A digital textile printer comprises a transfer belt 200
with a rail shape on the top of a base 110 supported by
both legs 100 contacted with the ground. The transfer belt
200 is combined with a cartridge (not shown), while the
cartridge is movable through the transfer belt and a head
15 unit (not shown) is fixed with the one side of the
cartridge.

As shown in Fig. 6, a driving panel 120 at the top of
the one side of the base 110 comprises a transfer motor 121
and a transfer axis 122. The transfer axis 120 is combined
20 with a transfer motor 121, and installed in long direction
within the base 110. As shown in Fig. 3, the transfer axis
122 includes multiple transfer rollers 123 protruding to
the top of the base 110. A press rod 124 is on the top of

<DELETED>

5

10

15

20

the transfer roller 123, and each press rod 124 corresponds to each transfer roller 123 respectively to transfer a printing material 800 to the forward direction. A handle lever 126 comprised in an operation panel 130 drives the
5 press rod 124.

As shown in Fig. 5, a rear feeding device 600 installed in the rear of the base 110 comprises a rear tension means 610, at the bottom of the rear of the leg 100, rotatable eccentrically in a predetermined angle. A rear position
10 sensor 616 corresponding to a rear eccentric axis 615 winding the printing material 800 is installed in a predetermined position of the top of the tension means 610. A feeding roller means 630 on the top of the rear tension means 610 comprises a bobbin axis 631 coupled with a bobbin
15 (not shown) winding the printing material 800, and a feeding motor 632 driven by signals from the rear position sensor 616.

The rear tension means 610 comprises rear fixtures 611 facing each other at the rear of both legs 100, two rear
20 brackets 612 with a predetermined length, a bearing 613, a rotation axis 614, and a rear eccentric axis 615. While the rotation axis 614 is installed in eccentric between two rear brackets 612, the one end of the rotation axis 614 is

<DELETED>

5

10

15

20

connected with the rear fixture 611, and the other end of the rotation axis 614 is connected with the bearing 613. In more, the rear eccentric axis 615 corresponding to the printing material 800 is between two rear brackets 612, and
5 maintains a predetermined distance from the rotation axis 614.

In other words, when the printing material 800 is wound to make the rear bracket 612 lifted up to the direction of the arrow mark in Fig. 7, and the rear position sensor, 616
10 detects the rear bracket 612 like the dotted line in Fig. 7. Sequentially, the rear position sensor 616 receives signals to rotate the feeding motor 632, and supplies the printing material 800 in the bobbin coupled with the bobbin axis 631 to the forward direction. As a result, the rear eccentric
15 axis 615 of the rear tension means 610 falls down to the downward direction like the solid line in Fig. 7.

In more, multiple adjusting holes 618 are formed between two rear brackets 612, and a rear tension adjusting axis 617 installed in one of the multiple adjusting holes 618 is
20 controlled to be balanced with the weight of the rear eccentric axis 615, and eventually to adjust tension strength of the rear eccentric axis 615.

As shown in Fig. 5 and Fig. 6, a rear guiding roller

<DELETED>

5

10

15

20

means 640 linked with the transfer axis 122 and installed in the rear of the base 110, comprises a first roller 642, a second roller 643, and a third roller 644 in two brackets 641 of both sides of the base 110 in adjacent and in a predetermined height difference. In more, pulleys 642a and 643a of the first and the second rollers 642 and 643 are coupled with a pulley 125 of the transfer axis 122 by means of a belt 646. Pulleys 645a and 647a of two tension axes 645 and 647 installed in a bracket 641 are connected with the belt 646, and make the belt 646 maintain constant tension force always.

As described in the above statements, the existing transfer axis 122 is used to drive the rear feeding device 600. Therefore, it is possible to embody a simple structure of the printing machine and to lower raw costs of manufacturing the printing machine.

As shown in Fig. 3, a front rewinding device 500 installed in the front of the base 110 comprises a front tension means 510, at the bottom of the front of the leg 100, roatable eccentrically in a predetermined angle. A front position sensor 516 corresponding to a front eccentric axis 515 winding the printing material 800 is installed in a predetermined position of the top of the

PCT/KR2004/002061

IPEA/KR 17.03.2005

<DELETED>

5

10

15

20

front tension means 510. A rewinding roller means 550 on the top of the front tension means 510 comprises a bobbin axis 551 coupled with a bobbin (not shown) winding the printing material 800, and a rewinding motor 552 driven by
5 signals from the front position sensor 516.

The front tension means 510 comprises front fixtures 511 facing each other at the front of both legs 100, two front brackets 512 with a predetermined length, a bearing 513, a rotation axis 514, and a front eccentric axis 515. While
10 the rotation axis 514 is installed in eccentric between two front brackets 512, the one end of the rotation axis 514 is connected with the front fixture 511, and the other end of the rotation axis 514 is connected with the bearing 513. In more, the front eccentric axis 515 corresponding to the
15 printing material 800 is between two front brackets 512, and maintains a predetermined distance from the rotation axis 514.

In more, multiple adjusting holes 518 are formed between two front brackets 512, and a front tension adjusting axis
20 517 installed in one of the multiple adjusting holes 518 is controlled to be balanced with the weight of the front eccentric axis 515, and eventually to adjust tension strength of the front eccentric axis 515.

<DELETED>

5

10

15

20

As shown in Fig. 3 and Fig. 6, a front guiding roller means 530 linked with the transfer axis 122 and installed in the front of the base 110, comprises a first roller 532 and a second roller 533 in two brackets 531 of both sides of the base 110 in adjacent and in a predetermined height difference. In more, a pulley 532a of the first roller 532 is coupled with the pulley 125 of the transfer axis 122 by means of a belt 540. In other words, the existing transfer axis 122 is used to drive the front rewinding device 500 without extra driving means. Therefore, it is possible not only to embody a simple structure of the printing machine, but also to maintain high accuracy.

As shown in Fig. 7, because of loads of the front eccentric axis 515 of the front tension means 510 and of the rear eccentric axis 615 of the rear tension means 610, the printing material 800 between them is tightened. Therefore, distortion or wrinkle of the printing material 800 is prevented. In more, the diameter of the first roller 532 of the front guiding roller means 530 is slightly larger than that of the first roller 642 of the rear guiding roller means 640. Therefore, the printing material 800 is pulled out to the front direction by constant force.

As shown in Fig. 3, it is preferable to form a long ink-

<DELETED>

5

10

15

20

retrieving hole 140 on the top of the base 110 to collect the residues of the injected ink passing through the printing material 800. As shown in Fig. 4, it is preferable to form at least one suction pan 150 in the inside of the
5 base to collect easily the residues of the injected ink passing through the printing material 800, and to form a heater 160 of rubber material at the bottom of the base 110 to dry promptly the printing material 800 passing through the ink-retrieving hole 140.

10 Operations of the digital textile printing machine of the present invention will be described in the following statements.

To install the printing material 800 to the digital textile printing machine, the printing material 800 is
15 pulled out from the bobbin combined with the bobbin axis 631 of the feeding roller means 630 at first, as shown in Fig. 5. Sequentially, the edge of the printing material 800 passes through the rear eccentric axis 615 of the rear tension mean 610, the third roller 644, the second roller
20 643, the first roller 642, the base 110, the first roller 532, the second roller 533, the front eccentric axis 515, and finally the bobbin axis 551 of the rewinding roller means 550, as shown in Fig. 7

<DELETED>

5

10

15

20

When the digital textile printing machine is operated, the transfer axis 122 linked with the transfer motor 121 in the driving panel 120 becomes to rotate, and the transfer roller 123 of the transfer axis 122 makes the printing material 800 move to the forward direction. Simultaneously, the first rollers 532 and 642 and the second roller 643 of the front and the rear guiding roller means 530 and 640 linked with the transfer axis 122 also rotate to make the printing material 800 move to the forward direction.

Meanwhile, the rewinding motor 552 of the rewinding roller means 550 rotates to wind the printing material to the bobbin like the solid line in Fig. 7. At this moment, the rotation of the rewinding motor 552 lifts up the bracket 512 including the front eccentric axis 515. Simultaneously, when the bracket 512 reaches to the position of the front position sensor 516, signals is sent to the front position sensor 516 to suspend rotation of the rewinding motor 552.

As shown in Fig. 7, because of loads of the front eccentric axis 515 of the front tension means 510 and of the rear eccentric axis 615 of the rear tension means 610, the printing material 800 between them is tightened. Therefore, distortion or wrinkle of the printing material

PCT/KR2004/002061

IPEA/KR 1 7. 0 3. 2005.

<DELETED>

5

10

15

20

800 is prevented. In more, the diameter of the first roller 532 of the front guiding roller means 530 is slightly larger than that of the first roller 642 of the rear guiding roller means 640. Therefore, the printing material
5 800 is pulled out to the front direction by constant force.

In more, when the printing material 800 is wound to make the rear bracket 612 lifted up to the direction of the arrow mark in Fig. 7, and the rear position sensor 616 detects the rear bracket 612 like the dotted line in Fig. 7.
10 Sequentially, the rear position sensor 616 receives signals to rotate the feeding motor 632, and supplies the printing material 800 in the bobbin coupled with the bobbin axis 631 to the forward direction. As a result, the rear eccentric axis 615 of the rear tension means 610 falls down to the
15 downward direction like the solid line in Fig. 7.

In other words, the rewinding motor 552 winds the printing material 800 only when the front position sensor 516 sends signals to the rewinding motor 552. In more, the feeding motor 632 supplies the printing material 800 only
20 when the rear position sensor 616 sends signals to the feeding motor 632. Such processes are repeated over and over again.

The ink-retrieving hole 140 is formed on the top of the

base 110 to collect effectively the residues of the injected ink passing through the printing material 800 to prevent ink from spreading, as shown in Fig. 3, and the suction pan 150 in the inside of the base 110 collects easily the residues of the injected ink passing through the printing material 800, as shown in Fig. 4. In more, the heater 160 in the inside of the front of the base 110 dries promptly the printing material 800 simultaneously.

As described in the above statements, the digital textile printing machine of the present invention comprises the front rewinding and the rear feeding devices 500 and 600 driven by the transfer axis 122 within the driving panels of the front and the rear of the base 110. Therefore, the printing material 800 is wound in a roller in the states of constant tension forces to prevent distortion and wrinkle phenomena generating defective printing. As a result, it is possible to perform effectively the textile printing even to the very thin textile fabrics.

Additionally, the digital textile printing machine of the present invention comprises a long ink-retrieving hole 140 along to the transfer axis 122 on the top of the base 110 to collect the residues of the injected ink passing through the printing material 800 to prevent ink from

spreading at the printing material 800.

In more, the digital textile printing machine of the present invention comprises at least one suction pan 150 in the inside of the base 110 to collect easily the residues
5 of the injected ink to hasten dries of ink.

In more, the digital textile printing machine of the present invention comprises the heater 160 of rubber material in the inside of the front of the base 110 to hasten dries of the printing material 800 passing through
10 the ink-retrieving hole.

While the invention has been particularly shown and described with reference to preferred embodiments thereof, it will be understood by those skilled in the art that the foregoing and other changes in form and details may be made
15 therein without departing from the spirit and scope of the invention.

What is claimed is:

1. A digital textile printer with a transfer belt with a rail shape on the top of the base supported by both legs contacted with the ground, a cartridge transferable through the transfer belt and fixing a head unit at the one side of the cartridge, a transfer axis with a long shape coupled with a transfer motor in a driving panel installed on the top of the inside of a base, multiple transfer rollers of the transfer axis protruding to the top of the base to make a printing material move to the forward direction, a feeding roller means installed in the rear of the base sending the printing material through the top of the base, a rewinding roller means rewinding the printing material from the top of the base, comprising:

15 at least one rear guiding roller means at the rear of the base, coupled with the transfer axis;

a rear feeding device including a rear tension means at the bottom of the rear of the legs to rotate eccentrically in a predetermined angle, a rear position sensor installed at a predetermined position of the rear tension means to correspond to a rear eccentric axis of the rear tension means winding the printing material, and a feeding motor installed on the top of the rear tension

means to drive a rear bobbin axis of the feeding roller means combined with a rear bobbin feeding the printing material by receiving signals from the rear position sensor;

5 at least one front guiding roller means at the front of the base, linked with the transfer axis; and

a front rewinding device including a front tension means at the bottom of the front of the legs to rotate eccentrically in a predetermined angle, a front position
10 sensor installed at a predetermined position of the front tension means to correspond to a front eccentric axis of the front tension means winding the printing material, and a rewinding motor installed on the top of the front tension means to drive a front bobbin axis of the rewinding roller
15 means combined with a front bobbin rewinding the printing material by receiving signals from the front position sensor.

2. The digital textile printer according to claim 1,
20 wherein the front/rear tension means installed at the front/rear of the bottom of the legs, comprises:

front/rear fixtures facing each other at the front of two legs;

a front/rear rotation axis installed eccentrically between two front/rear brackets with a predetermined length, penetrating two front/rear brackets, and both ends of the front/rear rotation axis combined with the front/rear
5 fixtures; and

a front/rear eccentric axis, corresponding to the printing material, apart in a predetermined distance from the front/rear rotation axis between the two front/rear brackets.

10

3. The digital textile printer according to claim 1, wherein the front/rear guiding roller means further comprises multiple front/rear rollers coupled with the transfer belt of the transfer axis and combined with at
15 least one front/rear tension axis.

4. The digital textile printer according to claim 1, wherein the diameter of the front roller of the front guiding roller means linked directly with the transfer axis
20 is slightly larger than the diameter of the rear roller of the rear guiding roller means.

5. The digital textile printer according to claim 1, further comprises an ink-retrieving hole in a long shape on the top of the base to collect the residues of the injected ink passing through the printing material.

5

6. The digital textile printer according to claim 1, further comprises a heater of rubber material at the inside of the base to dry promptly the printing material.

10 7. The digital textile printer according to claim 1, further comprises:

multiple front/rear adjusting holes between the two front/rear brackets; and

15 a front/rear tension adjusting axis installed in one of the multiple front/rear adjusting holes to balance with the weight of the front/rear eccentric axis, and eventually to adjust tension strength of the front/rear eccentric axis.

20

ABSTRACT OF THE DISCLOSURE

The present invention discloses a digital textile printer including a front and a rear feeding devices driven by a transfer axis within a driving panel of the front and
5 the rear of a base to prevent distortion and wrinkle phenomena generating defective printing to perform effectively the textile printing even to the very thin textile fabrics, an ink-retrieving hole along to the transfer axis on the top of the base to collect the
10 residues of the injected ink passing through a printing material to prevent ink from spreading at the printing material, at least one suction pan in the inside of the base to collect easily the residues of the injected ink to hasten dries of ink, and a heater of rubber material in the
15 inside of the front of the base to hasten dries of the printing material passing through the ink-retrieving hole.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.